

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 November 2002 (21.11.2002)

PCT

(10) International Publication Number
WO 02/092219 A1

(51) International Patent Classification⁷: **B01J 19/00**,
G01N 31/10

(21) International Application Number: PCT/EP02/05321

(22) International Filing Date: 13 May 2002 (13.05.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/290,031 11 May 2001 (11.05.2001) US
01201739.8 11 May 2001 (11.05.2001) EP

(71) Applicant (for all designated States except US): **AVANTIUM INTERNATIONAL B.V.** [NL/NL]; Zekeringstraat 29, NL-1014 BV Amsterdam (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **VAN DEN BRINK, Peter, John** [NL/NL]; Rijsenburgselaan 22, NL-3972

EJ Driebergen (NL). **BRACHT, Maarten** [NL/NL]; Borneokade 165, NL-1019 XD Amsterdam (NL). **HARJI, Bashir, Husein** [GB/GB]; 7 The Rowells, Cottenham CB4 8XJ (GB).


(74) Agent: **BROOKHUIS, H., J., A.**; Exter Polak & Charlois B.V., P.O. Box 3241, NL-2280 GE Rijswijk (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SYSTEM SUITABLE FOR HIGH THROUGHPUT EXPERIMENTATION



(57) Abstract: A system for performing experiments, in particular for high throughput experimentation. The system comprises a tubular vessel allowing a flow of fluid through said vessel and an assembly for housing said vessel. The assembly comprises a base block having a first channel formed therein for removably housing the vessel, said first channel having first and second channel openings allowing introduction and/or discharge a fluid into and from said first channel. The assembly also comprises a cover element having a bottom surface being releasably attachable to the first face of the base block. A first sealing element is provided between the first face of the base block and the bottom surface of the cover element, the first sealing element surrounding the first channel opening completely, and thereby sealing gastight around said first channel opening between the cover element and the base block. The system further comprises a second sealing element located in the first channel, said second sealing element sealing gastight against the inside of the first channel and the outside of the vessel.



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SYSTEM SUITABLE FOR HIGH THROUGHPUT EXPERIMENTATION

The present invention relates to a system for performing experiments, in particular for high throughput experimentation. Systems for high throughput experimentation ("HTE") are known and are used for simultaneously conducting a large number of experiments using a plurality of vessels, optionally with different reaction conditions. High throughput experimentation is used for instance in the pharmaceutical industry for the discovery and development of new and useful drugs and in the field of catalysts for the development of new catalysts (see e.g. Angew. Chem. Int. Ed. 1999, 38, No.18, pp 2794-2803).

The object of the invention is to provide an improved system.

The invention provides a system according to claim 1. In this system a flow of fluid from one end of the first channel to the other end has to pass through the tubular vessel as the second sealing element prevents a bypass flow between these ends along the outside of the vessel.

It will be understood that multiple second sealing elements can be provided along a part of the length of the vessel, e.g. a cluster of adjacent second sealing elements.

The second sealing element(s) can be fitted on the vessel or in the base block, or form part of a separate fitting to be mounted between the vessel and the inside of the first channel.

Preferably an annular gap is present between (a part of) the outside of the vessel and the inside of the first channel. The second sealing element(s) shuts off this gap at the location of said second sealing element.

The presence of an annular gap has multiple advantages. For instance the gap allows for diametrical expansion of the vessel (e.g. thermal expansion) without the vessel become stuck in the first channel. Also the annular gap prevents the vessel to become stuck in the first channel due to corrosion or intrusion of particles between the vessel and the inside of the first channel.

Also the gap allows for a fluid flow along parts of the length of the vessel between the second sealing element and one or both ends of the vessel as will be explained further below.

5 The first channels of the system according to the present invention are described herein as having first and second openings, opening in certain faces of the base block. The person skilled in the art will readily understand that these first and second openings may be inlets or outlets, depending
10 on in which direction a fluid to be used flows. Usually, the first openings are inlets and the second openings outlets. For simplicity reasons, the first openings and second openings will be denoted as inlets and outlets respectively, throughout the description.

15 Furthermore, the person skilled in the art will readily understand that the first face and second face of the base block can be one and the same, i.e. the through going first channel may have both its inlet and outlet in the first face of the base block.

20 The first and second sealing elements used in the system according to the present invention may be O-rings. Such O-rings are not limited to a substantially circular cross-sectional form, but can have any suitable form for sealing, as will be well understood by a person skilled in the art. Further, the O-
25 rings can be made from any suitable material, such as metal or an elastomer. Instead of O-rings, the sealing elements may have any other suitable form known to the person skilled in the art. For example, multiple layers of tape or V-shaped metal rings may also be used.

30 According to a preferred embodiment of the system according to the present invention, the first sealing element is made from a high pressure resistant material, while the second sealing element is made from a resilient material such as for example rubber. Hereby, a very easy and gastight sealing
35 can be obtained.

 The selection of material of the sealing elements also depends on the temperatures present in the system, in particular of the base block. Usually, the temperature nearby the first face of the base block has a value allowing the

sealing elements to be made from a resilient, elastomeric material.

The first and second faces of the base block and the bottom surface of the cover element may have any suitable form, as long as, in attached condition of the base block and cover element, a sufficient sealing of the vessels is obtained.

According to a preferred embodiment of the system according to the invention, both or any of the first face of the base block and the bottom surface of the cover element are substantially planar. Hereby, a very easy and very effective gastight sealing of the vessels can be obtained.

As mentioned above and as will be illustrated more clearly in the drawings hereinafter, the second sealing element is located in the first channel of the base block and around the vessel placed in the base block. According to a preferred embodiment of the present invention, the second sealing element is located in the vicinity of the first face of the base block. Hereby it is ensured that the fluid, which is fed into the inlet of the vessel, will be maintained under substantially the same conditions. Furthermore, the occurrence of dead volume can be avoided.

According to an advantageous embodiment, the base block comprises at least one second channel connecting to the first channel of the base block between the second sealing element and the first channel opening. Hereby a fluid can be easily fed to (or removed from) the first channel opening.

It is preferred that the cover element comprises at least one third channel in fluid communication with the at least one first channel in the base block. Hereby feeding of the individual vessels can be provided for, while the contents of the individual vessels are isolated from the contents of any other vessel contained in the base block.

Further it is preferred that the base block comprises a fourth channel opening into the first channel of the base block between the second sealing element and the second channel opening. Hereby a fourth channel can be brought in fluid communication with the second vessel opening.

The fourth channel can be used for purging purpose when said channel is connected to a supply of purging fluid. For

example the fourth or purging channel can be brought in fluid communication with a pressurised source of an inert fluid such as N_2 . Hereby for example a product gas obtained by treatment in the vessel can be prevented from condensing by diluting said product gas by use of the inert fluid. Furthermore, the treatment process using the system as a whole can be accelerated as the product gas is more efficiently obtained.

Using a preferred embodiment of the system according to the present invention a plurality of vessels housed in a base block can be sealed simultaneously and in a very easy manner by attaching the cover element to the base block housing the vessels, whereby all vessels are sealed in a gastight manner.

The person skilled in the art will readily understand that further feeding channels, sealing elements, etc. may be provided.

Finally, the present invention relates to methods for operating the system according to the present invention.

Hereinafter, the present invention will be illustrated in more detail by a drawing. Herein shows:

Figure 1 a schematic cross-sectional view of a system according to the present invention in a partly assembled state;

Figure 2 a schematic cross-sectional view of an alternative system according to the present invention in assembled state;

Figure 3 a schematic cross-sectional view of a further alternative system according to the present invention in assembled state; and

Figure 4 a perspective view of a vessel.

In figure 1 a schematic cross-sectional view of a system according to the present invention is shown in partly assembled state. The system comprises an assembly 1 for housing a plurality of tubular vessels 2 of rectilinear shape having a first vessel opening (inlet 3) and a second vessel opening (outlet 4) at the opposite ends thereof. The vessels 2 may be embodied as tubes of metal or other suitable material.

The assembly 1 comprises a base block 5 and a cover element 9. The base block 5 has a plurality of through going

first channels 6 formed therein for removably housing the vessels 2.

The first channels 6 each have a first channel opening (inlet 19), opening in a first face 7 of the block 5 and a
5 second channel opening (outlet 18), opening in a second face 8 of the block 5.

The first channels 6 are formed here as bores in the solid base block 5. However other designs, wherein a first channel 6 is entirely or partly formed by a tubular part of the
10 base block 5 are also possible.

The vessels 2 have a length such that each vessel 2 is entirely accommodated within the first channel 6.

In figure 1 it can be seen that an extension channel 25
15 is formed extending coaxially and in line with the first channel 6. The extension channel 25 extends between the lower end of the first channel and the second face 8 of the base block 5. The extension channel 25 has a smaller diameter than the first channel 6, so that an annular shoulder 26 is formed.
20 The vessel 2 can be designed to rest upon this annular shoulder 26.

In a variant not shown here, both the inlet 19 and the outlet 18 may open into the first face 7 of the block 5.

25 In the embodiment of figure 1 the first face 7 of the base block 5 is facing towards the cover element 9. The cover element 9 is releasably attachable on the first face 7 of the base block 5. There may be fastening means provided, such as screws, to attach the cover element 9 to the base block 5.

30 Between the first face 7 of the base block 5 and the bottom surface 10 of the cover element 9, a number of high pressure resistant O-rings 11 are provided as first sealing elements. These O-rings 11 are placed such that the O-ring 11
35 is near the inlet 19 of the first channel 6 and surrounds this inlet 19. Hereby leakage between neighbouring first channels 6 is prevented.

As is shown, annular grooves are provided in the first face 7 of block 5 for receiving the O-ring 11. This also prevents movement of the O-rings 11 in case of a horizontal movement of the cover element 9. Alternatively, the annular
5 grooves may be provided in the bottom surface 10 of the cover element 9.

The assembly 1 is further provided with resilient O-rings 12 acting as second sealing elements. These O-rings 12 are
10 located in the first channels 6 of the base block 5.

In figure 4 it can be seen that the O-ring 12 is mounted on the outside of the tubular vessel 2, preferably located in a circumferential groove in the vessel 2. The second sealing
15 element 12 could also be integral with the wall of the vessel 2, such as a thin flexible annular lip extending around the circumference of the vessel.

As the diameter of the vessel 2 is less than the diameter
20 of the first channel 6 an annular gap is present between the outside of the vessel 2 and the wall of the first channel 6. The O-ring 12 is placed such that this annular gap is divided into two zones 13, 14. These two zones 13, 14 in the first channel 6 are sealed from each other in a gastight manner by
25 the sealing element 12 between them. Of course, fluid communication may take place between zone 13 and 14 via the vessel 2.

In a preferred embodiment the vessel 2 has at the side of the second opening 4 side openings 30 (see figure 4) to allow
30 fluid flow via the gap located below the second sealing element 12.

In the embodiment of figure 1, an easy and simultaneously sealing of the first channels 6 of the system can be obtained
35 by attaching the cover element 9 to the base block 5.

The first and second sealing elements 11, 12 may have any suitable form, as long as a sufficient sealing is obtained. For example the first sealing element 11 may be made of a high

pressure resilient (and, if desired, heat resistant) material such as a rubber, but may also be made of the same material as the base block 5 and cover element 9 (preferably a metal). The person skilled in the art will understand that the sealing element 11 may form part of the base block 5 or the cover element 9.

The second sealing element 12 is preferably made of a resilient material, for example an elastomeric material such as for instance rubber.

10

In figure 1 the cover element 9 is closed and has no internal channels connecting to the first channels 6. This allows the cover element 9 to be designed as a simple plate element.

15

In figure 1 additional second channels 20 are provided in the base block 5 for fluid communication with the inlet 3 of the vessels 2. These second channels 20 each connect to a first channel 6 between the second sealing element 12 and the first opening 19 of the first channel 6.

20

Figure 2 shows a schematic cross-sectional view of an alternative embodiment of the system shown in figure 1, in assembled state of the cover element 9 and the base block 5. Parts corresponding to the system of figure 1 have the same reference numerals.

25

The cover element 9 is provided here with third channels 15 each connecting to the inlet 3 of a vessel 2.

The vessels 2 each contain a reaction zone 17, for example containing a catalyst in the form of a catalyst bed.

30

The base block 5 according to the embodiment shown in figure 2 comprises fourth channels 16 opening into zone 14, i.e. the space in first channel 6 outside the vessel 2 and below the second sealing element 12.

35

The fourth channels 16 can be used for example for purging or diluting purposes. For example the fourth channel 16

may be in fluid communication with a pressurised source of an inert fluid such as N_2 .

To prevent condensing of the product obtained in the reactor zone 17, if a gaseous product is obtained, an inert gas such as N_2 can be fed by fourth channel 16 to force the product obtained in the experiment through the outlet 18 of first channel 6. Herewith a very easy diluting of the product gas can be obtained and condensing can be prevented.

10

In a possible application of the system of figure 2, a fluid to be treated is fed via third channel 15 to the inlet 3 of the vessel 2. This third channel 15 will of course usually be provided with further sealing means or valves to prevent the fed fluid from returning to the third channel 15. After passing the reactor zone 17 the treated fluid will enter the zone 14 and be discharged via outlet 18.

In practice second channels 20 are preferably used for feeding gaseous products whereas third channels 15 are preferably used for feeding liquid products. For the feeding of a liquid for instance a capillary may be used, which may be partially inserted in the third channel 15.

It will be apparent that the second and third channels 20 and 15 can also be used for discharging product, which has passed through a vessel 2.

Figure 3 shows a schematic cross-sectional view of a further alternative embodiment of the system according to the present invention.

30

The base block 5 has fourth channels 16, e.g. for purging purposes, and second channels 20, e.g. for feeding a fluid to the inlet 3 of the vessel 2.

In this embodiment the sealing elements 12 are located between the mouth of the second and fourth channels 20 and 16 respectively.

35

A sealing element 12 is placed in an annular groove in the wall of the first channel 6 to prevent movement of the

sealing element 12 when the vessel 2 is inserted or removed or under the influence of a pressure difference.

Furthermore, the assembly 1 in figure 3 has a fluid feed conduit 21 extending through a third channel 15 in the cover 9, such as a capillary, e.g. for feeding a liquid in the inlet 3 of the vessel 2. A sealing means 27 is provided here for sealing the passage of the conduit 21 through the cover element 9.

The assembly of figure 3 furthermore shows the possibility to arrange a second fluid conduit 28 such that it extends into the extension channel 25. The diluted reaction product can be removed via fourth channel 16 or via the now annular extension channel 25 connecting to outlet 29. Otherwise a fourth sealing means could be provided to seal the annular gap between the second fluid conduit 28 and the base block 5.

The second fluid conduit 28 could be designed as a capillary, e.g. for feeding a (diluting) fluid into the space below the vessel 2.

The second fluid conduit 28 could e.g. also be used for removing a sample of reaction product from the first channel 6. If the fluid flow through the vessel 2 were to be inversed the first fluid conduit 21 could be used for the same purposes.

The wall of the first channel 6 is provided with heating means 22 for locally heating the vessel 2, in this embodiment in particular the reactor zone 17.

In the embodiment shown in Figure 3, the reactor block 5 provides for such a heating that only the reactor zone 17 will be significantly heated, while other parts of the assembly may be maintained at a lower temperature.

Preferably the heating means 22 are designed such that the sealing elements 12 are allowed to be made from an elastomeric material, without being degraded by the heat generated by the heating means 22.

The person skilled in the art will understand that many modifications can be made. For instance, the assembly 1 may be provided with further heating means for obtaining a specific temperature in certain parts of the block 5. Also, flow rate regulating elements, such as capillaries may be incorporated in the vessels 2. Further, the person skilled in the art will understand that the invention is not limited to an embodiment wherein the cover element 9 lies upon the base block 5; the assembly 1 may also be configured such that the cover element 9 is positioned under or next to the base block 5. Further, the first channels 6 in the base block 5 may be in the form an array, i.e. comprising several rows of parallel first channels 6.

15

It will be apparent as an alternative to heating means or in combination therewith cooling means can be provided in order to cool (a part of) the vessel 2 and/or base block 5. In a preferred embodiment a cooling means is provided in the region of the inlet of the vessel, e.g. to prevent liquid entering the vessel from boiling at this location.

20

As will be clear from the above, the system according to the present invention provides for a very easy and simultaneous sealing of at least one, but usually pluralities of vessels.

25

As is mentioned above, the openings described as "inlet" may also function as outlet, depending on the flow direction of the fluid. This also applies for "outlet" which may, when desired and appropriate, function as inlet.

30

C L A I M S

1. A system for performing experiments, in particular for
5 high throughput experimentation, said system comprising:
- at least one tubular vessel (2) having a first vessel opening
(3) and a second vessel opening (4) at opposite ends thereof
allowing a flow of fluid through said vessel (2),
- an assembly (1) for housing said vessel, said assembly
10 comprising:
- a base block (5) having at least one first channel (6)
formed therein for removably housing the vessel (2),
said first channel (6) having a first channel opening
(19), opening in a first face (7) of the base block, and
15 a second channel opening (18), opening in a second face
(8) of the base block (5), said first and second channel
openings (19,18) allowing introduction and/or discharge
of a fluid into and from said first channel (6),
- a cover element (9) having a bottom surface (10), the
20 cover element (9) with the bottom surface (10) facing
the base block (5) being releasably attachable to the
first face (7) of the base block (5);
- a first sealing element (11) between the first face (7)
of the base block (5) and the bottom surface (10) of the
25 cover element (9), the first sealing element (11)
surrounding the first channel opening (19) completely,
and thereby sealing gastight around said first channel
opening (19) between the cover element (9) and the base
block (5);
30 and said system further comprising:
- a second sealing element (12) located in the first channel
(6), said second sealing element (12) sealing gastight
against the inside of the first channel (6) and the outside
of the vessel (2).
35
2. A system according to claim 1, wherein an annular gap is
present between the outside of the vessel (2) and the inside of

the first channel (6), and wherein said second sealing element (12) seals said annular gap.

3. A system according to claim 2, wherein said gap is
5 between 0.01 and 1 millimetres, preferably between 0.02 and 0.5 millimetres, most preferably between 0.05 and 0.2 millimetres.

4. A system according to one or more of claims 1-3,
wherein the second sealing element (12) is located in the
10 vicinity of the first face (7) of the base block (5).

5. A system according to any of the preceding claims,
wherein said second sealing element (12) is mounted on the
tubular vessel (2).
15

6. A system according to any of the preceding claims,
wherein the base block (5) comprises a second channel (20)
connecting to the first channel (6) between the second sealing
element (12) and the first channel opening (19).
20

7. A system according to any of the preceding claims,
wherein the cover element (10) comprises a third channel (15),
in fluid communication with the at least one first channel (6)
in the base block (5).
25

8. A system according to any of the preceding claims,
wherein the base block (5) comprises a fourth channel (16)
connecting to the first channel (6) between the second sealing
element (12) and the second channel opening (18).
30

9. A system according to any of the preceding claims,
wherein the vessel contains a reaction zone, for example
containing a catalyst.

35 10. A system according to any of the preceding claims,
wherein the first face (7) of the base block (5) and the bottom
surface (10) of the cover element (9) are substantially planar.

11. A system according to any of the preceding claims, wherein heat exchange means are provided for controlling the temperature of a part of the vessel (2) and/or the base block (5).

5

12. A system according to claim 11, wherein heating means are provided for locally heating the vessel.

13. A system according to claim 9, wherein the heating means are mounted in the base block (5), preferably for heating a reaction zone (17) of the vessel.

14. A system according to any of the preceding claims, wherein said base block has multiple first channels (6) each housing a vessel (2).

15. A system according to claim 14, wherein a single cover element (9) covers the first face of the base block and thereby the first channel openings of all first channels (6).

20

16. A system according to claim 8, wherein the system comprises a means for feeding a fluid, e.g. a purging fluid, via said fourth channel (16) into the first channel (6).

17. A system according to one or more of the preceding claims, wherein the first face (7) of the base block is opposite from the second face (8), and wherein the second channel opening (18) is formed by an extension channel (25), extending coaxial in line with said first channel (6) and opening into said second face (8).

30

18. A system according to claim 17, wherein said extension channel (25) has a smaller diameter than said first channel (6), thereby forming an annular shoulder (26).

35

19. A system according to claim 18, wherein the vessel (2) is supported by said annular shoulder (26).

20. A system according to claim 7, wherein a first fluid conduit (21) extends through said third channel (15) and is in communication with said first channel opening (19), and wherein a third sealing means (27) can be provided between the first
5 fluid conduit (21) and the cover element (9).

21. A system according to claim 17, wherein a second fluid conduit (28) extends through said extension channel (25) and is in communication with said second channel opening (18), and
10 wherein a fourth sealing means (29) can be provided between the second fluid conduit (28) and the base block (5).

22. A method for performing an experiment, wherein use is made of a system according to one or more of the preceding
15 claims.

23. A method for performing an experiment using the system according to claim 16, wherein a purging fluid is fed through said fourth channel (16) before an experimentation fluid is
20 allowed to flow through said vessel (2).

24. A method for operating the system according to claim 16, wherein an experimentation fluid is introduced into the vessel (2) via the first opening (3) thereof and a reaction
25 product is discharged from said second opening (4) of the vessel (2) and wherein a diluting fluid for diluting the reaction product is fed through said fourth channel (16).

25. A method for operating the system according to claim
30 21, wherein a diluting fluid is introduced into the first channel (6) via second fluid conduit (28) or via the extension channel (25).




Fig 1




Fig 2




Fig 3




Fig 4

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 02/05321

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B01J19/00 G01N31/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B01J G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 866 342 A (KULIKOV NICOLAY ET AL) 2 February 1999 (1999-02-02) column 5, line 19 - line 51; figures 4,4A ---	1-5,7, 9-14,17, 20-22,25
A	US 4 787 988 A (BERTONCINI JOSEPH ET AL) 29 November 1988 (1988-11-29) column 6, line 22 -column 7, line 27; figure 2 ---	1
A	WO 97 09353 A (PATHOGENESIS CORP ;BAKER WILLIAM R (US); HARNESS JAMES R (US); TOW) 13 March 1997 (1997-03-13) page 7, line 12 -page 9, line 8 page 10, line 9 - line 19; figures 1,3A,5 --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

17 September 2002

Date of mailing of the international search report

25/09/2002

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Veefkind, V

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/05321

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 5 714 127 A (DEWITT SHEILA H H ET AL) 3 February 1998 (1998-02-03) abstract; figures 1-4,9,16,19</p>	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

In tional Application No

PCT/EP 02/05321

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5866342	A	02-02-1999	AU 4705697 A WO 9813137 A1 US 6238929 B1	17-04-1998 02-04-1998 29-05-2001
US 4787988	A	29-11-1988	NONE	
WO 9709353	A	13-03-1997	AU 6916396 A CA 2231170 A1 EP 0848721 A1 JP 11502720 T WO 9709353 A1 US 5716584 A	27-03-1997 13-03-1997 24-06-1998 09-03-1999 13-03-1997 10-02-1998
US 5714127	A	03-02-1998	US 5612002 A US 5324483 A US 5593642 A US 5565173 A US 5582801 A US 5567391 A US 5702672 A US 5766556 A AU 5355894 A EP 0663856 A1 JP 8502482 T MX 9306219 A1 WO 9408711 A1	18-03-1997 28-06-1994 14-01-1997 15-10-1996 10-12-1996 22-10-1996 30-12-1997 16-06-1998 09-05-1994 26-07-1995 19-03-1996 29-04-1994 28-04-1994

